

Description

The 4310 fused magnet safety disconnect switch is designed to safely allow the operator of a lifting magnet to disconnect the highly inductive magnet while the magnet is still energized. Standard safety switches are not designed to safely disconnect an energized magnet.

The 4310 has (3) power poles. Two normally open power poles to disconnect the incoming power and a third normally closed power pole that shunts the magnets energy into a discharge resistor when the disconnect is switched to the off position.



Features

- Supplied in a NEMA type 3R wall mounting enclosure.
- Rated 300 VDC. Max
- All switches have a padlockable thru-the-door operator
- High capacity discharge resistor

Part Number	Fused At	Magnet Amps (Max)	Enclosure Dimensions			List Price ET
			H	W	D	
4310-86262-004	100 Amps	67	29.00	12.63	10.00	\$2,850
4310-86262-002	200 Amps	134	29.00	12.63	10.00	\$3,375
4310-86273-001	400 Amps	267	31.25	24.00	13.29	\$9,195

How To Order
Specify magnet operating current, cold.
Enclosure type is NEMA 3R
Order by part number



Hubbell Industrial Controls, Inc.

A subsidiary of Hubbell Incorporated

4301 Cheyenne Dr., Archdale, NC. 27263

Telephone (336) 434-2800 • FAX (336) 434-2803

<http://www.hubbell-icd.com>

Sales@hubbell-icd.com